

## Breathable Air Systems

### Breathable Air Filtration

Also includes  
½" ball valve  
shutoff for easy  
maintenance

| Order No. | Model No. | Description                                        | Removes<br>Dirt to<br>5 Micron         | Removes<br>Liquid<br>Water             | Removes<br>Oil<br>Aerosols             | Removes<br>Humidity         | Removes<br>Odor |
|-----------|-----------|----------------------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|-----------------------------|-----------------|
| 130089    | DAD-503   | 3-stage filtration with dessicant air dryer system | Yes                                    | Yes                                    | Yes                                    | Yes                         | Yes             |
| 130087    | HAF-601   | 3-stage filtration system                          | Yes                                    | Yes                                    | Yes                                    | No                          | Yes             |
| 130096    | DAD-504   | Dessicant retrofit system                          | Yes, when used with DAD-500 or HAF-518 | Yes, when used with DAD-500 or HAF-518 | Yes, when used with DAD-500 or HAF-518 | Yes, when used with DAD-500 | Yes             |



# DeMask™



## OV/N95 Reusable Multi-Purpose Respirator

| Part Number   | Order Number | Description                                    |
|---------------|--------------|------------------------------------------------|
| 40-362        | 310000       | DeMask Half Mask Resp OV/N95 Md/Lg             |
| 40-365-K2     | 310001       | DeMask Half Mask OV/N95 Cartridge - 2 pk       |
| 40-366-K10    | 310002       | DeMask Half Mask Pre-Filter - 10pk             |
| 40-365-K2-10  | 310003       | DeMask Half Mask OV/N95 Cartridge - 10 pk of 2 |
| 40-366-K10-10 | 310004       | DeMask Half Mask Pre-Filter - 10 pk of 10      |

**NIOSH**



### High Performance and Superior Comfort

- Provides minimum 95% efficiency against most organic vapors
- Low-profile design fits under safety glasses and face shields
- Rolled sealing flange provides superior comfort and improved fitment
- Large inhalation/exhalation valves allow for maximum airflow in and out of mask
- Adjustable design fits almost all users with one size



## Dad-Pro™ Desiccant Air Drying System



### Worry Free Air Filtration for Top-Quality Paint Jobs

- First stage filter removes oil, water and dirt down to 5 microns.
- Second stage coalescer removes oil vapors and dirt particles down to .01 microns.
- Desiccant tank removes water vapor and humidity down to a dew point of -40° F.
- Bagged desiccant and automatic drains for ease of maintenance.

| Order No. | Description                                |
|-----------|--------------------------------------------|
| 130546    | DAD-PRO Desiccant Air Drying System        |
| 130504    | Replacement Desiccant Cartridge            |
| 130536    | 50 scfm 2-Stage Filter Assy with Regulator |
| 130538    | Replacement Water Separator Element        |
| 130539    | Replacement Oil Coalescing Element         |
| 130544    | Filter Mounting Bracket                    |
| 130545    | Float Drain Kit                            |



**130536 130536  
CAMAIR® 50 SCFM  
2 STAGE & REG**



**Replaceable Desiccant  
Cartridge for Easy  
Maintenance**

## Dad-500™ Desiccant Air Dryer System



### Avoid Costly Re-dos

- Properly maintained air filtration system eliminates moisture and dirt in air lines
- Install at point of use

| Order No. | Model No. | Description                        |
|-----------|-----------|------------------------------------|
| 130026    | DAD-500   | 3-stage desiccant air dryer system |



**Compare DeVilbiss filtered air vs. unfiltered air DeVilbiss'**  
DAD-500 filters out contaminants to .01 micron

**CleanAir = Better Finish**



**Compare the humidity reading before and after filtering with DeVilbiss DAD-500**



**READING BEFORE FILTERING**  
(70.2% Relative humidity)



**READING AFTER FILTERING**  
(.2% Relative humidity)

## Ct30 & Ct30p Desiccant Cartridge Dryers



### Easy Change Desiccant Air Dryer

- CT series desiccant air dryers remove water vapor from the compressed air down to a dew point of -40° F
- Quick change 10 lb. desiccant cartridge bag is made of a special fiber media which removes oil aerosols and solid particles down to 0.1 micron meaning no need for coalescing or final filters
- Install at point of use
- 30 CFM air flow capacity

| Order No.     | Description                             |
|---------------|-----------------------------------------|
| <b>130500</b> | Desiccant Air Dryer wall mount          |
| <b>130501</b> | Desiccant Air Dryer portable with stand |
| <b>130504</b> | Desiccant Cartridge                     |



## Camair Qc3 Filter and Dryer Unit



### A Great Choice for Light Usage Such as Low Volume Shops, Restorers, Customizers, and Hobbyists

- Three-stage filtering with 0.1 micron rating produces clean, oil- and humidity-free air.
- High performance filtration with only 2 PSI pressure drop.
- Quick change filter cartridge is easy to maintain. Bowl removal tool included.
- Larger filter media and longer life desiccant than disposable dryers
- Install at point of use

| Order No.     | Description                                    |
|---------------|------------------------------------------------|
| <b>130525</b> | Desiccant Filter and Dryer Unit                |
| <b>130524</b> | QC3 Filter and Desiccant Cartridge Replacement |





## Air Filtration/Regulation Systems

- Compact and effective—perfect for cramped shop spaces
- Removes dirt, water and oil from air lines to 0.01 micron—assures superior finishes
- Quick change bowls and air inlet valve accommodate rapid, trouble free maintenance without shutting off main shop air
- Combine 2-stage filter with the CT-30 desiccant dryer to create a CT Plus 5-stage filter system
- 65 SCFM @ 90 PSIG

130523  
2-Stage w/Regulator



| Order No. | Description                        |
|-----------|------------------------------------|
| 130523    | 2-stage filter unit with regulator |

## Automatic Drain With Y-Strainer Valve



### Automatically Drains Water from Compressed Air Systems

| Order No. | Description                           |
|-----------|---------------------------------------|
| 130512    | Automatic drain with Y-strainer valve |

- Use with air compressors, water separators and at drop legs
- Adjustable interval time and drain time
- Removable filter for easy cleaning
- Includes electric timer, 1/4" Y-strainer valve with filter screen and 6 ft. power cord

## CT Plus™ 5-Stage Filter System



### Complete Compressed Air Treatment and Drying Center

### Worry Free Air Filtration for Top Quality Paint Jobs

- First stage filter removes oil, water and dirt down to 40 micron
- Second stage coalescer removes oil vapors and dirt particles down to .01 micron
- CT30 desiccant tank repeats dirt and oil aerosol removal and removes humidity

| Order No. | Description                             |
|-----------|-----------------------------------------|
| 130522    | CT Plus 5-stage desiccant filter system |
| 130517    | Filter element, water (1st stage)       |
| 130518    | Filter element, coalescing (2nd stage)  |
| 130504    | DC30 desiccant cartridge                |

### 30 CFM Air Flow Capacity

- Longer desiccant life
- Air inlet valve shuts off CT Plus™ air without having to shut off shop air
- No tools needed to change first and second stage filters
- Easy change-out desiccant cartridge bag

### Ergonomic, Self-Relieving Regulator



## Clean Air™ Air Line Filters and Control Units

**Air Filtration  
and Regulation Systems  
Remove Dirt, Oil Vapor,  
and Water from Air Lines**

### HAF-518 Quick Facts:

- 1st Stage 5 micron filter
- 2nd Stage .01 micron filter
- Easier maintenance comes with manual flexible drain



| Order No. | Model No. | Description                                                                          |
|-----------|-----------|--------------------------------------------------------------------------------------|
| 130098    | HAF-518   | Two-stage filtration system, including centrifugal and coalescer w/ 60 CFM regulator |
| 130041    | 13-0041   | 100 CFM air line filter                                                              |
| 130042    | 13-0042   | 100 CFM air line filter w/ 60 CFM regulator                                          |

### ACCESSORIES

130093 / HAR-600  
60 CFM regulator w/gauge

190771 / HAF-18  
Automatic drain



## Whirlwind™ Disposable Air Filter

| Order No. | Model No. | Description                      |
|-----------|-----------|----------------------------------|
| 130028    | HAF-507   | Whirlwind Filter (order qty. 12) |

**DeVilbiss Whirlwind: Longer Life  
and Less Pressure Drop**

### Patented Two-Stage Filter:

#### Stage 1—

#### Swirl Chamber:

Removes large water droplets

#### Stage 2—

#### Filter Media:

Removes smaller water droplets, oil droplets, and dirt particles



Can be used with all HVLP spray guns

### All Other Competitive Filters:

- Water droplets saturate the filter media — shortening the life of the filter
- Smaller inlet surface area increases pressure drop

## Finishline® Air Control Unit



**FINISHLINE**  
by DeVilbiss

### Includes:

- 5 micron particle filter
- Mounting bracket
- Regulator and gauge

### The Value Leader

- Removes moisture and dirt
- Regulates air pressure

| Order No. | Model No. | Description                                   |
|-----------|-----------|-----------------------------------------------|
| 130099    | HAR-602   | 120 CFM air line filter w/ 50 CFM regulator   |
| 192315    | HAF-39    | 120 CFM Filter element and gasket kit         |
| 803643    | HAR-680   | 80 CFM air control unit with 50 CFM regulator |
| 803641    | HAF-47    | 80 CFM Filter element and gasket kit          |

### ACCESSORIES

192314 / GA-375  
Gauge for HAR-520 regulator

192315 / HAF-39  
HAR-602 Element Kit

130100 / HAR-520  
50 CFM regulator for HAR-602

